


NOTES:

- MATERIAL:**
 BODY: HI-TEMP. PLASTIC, BLACK, UL 94V-0
 TERMINAL: COPPER ALLOY, T=0.10mm
 SHELL: STAINLESS STEEL
- FINISH:**
 TERMINAL: 50μ" Ni MIN UNDER PLATING OVER ALL
 GOLD FLASH ON CONTACT AREA
 TIN 60-200μ" PLATED ON SOLDER TAIL AREA
 SHELL: 50μ" Ni MIN UNDER PLATING OVER ALL
 AU 1~3μ" PLATED ON SOLDER TAIL AREA
- ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
- ALL DIMENSIONS MARKER (XX) MUST BE MEASURED BY FAI.
- GP PASSED ACCORD WITH HRD-RoHS-219 STANDARD.

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO: B52-AB03F14C
				DATE: 03/24/2014	X. ±0.25	X." ±2.00'	CHECKED:	TITLE: 1.4H 测压式的Battery
				SCALE: 10:1	.XX ±0.10	.XX" ±0.50'	APPROVE:	DRAWING NO:
					.XXX ±0.05	.XXX" ±0.10'		
B	E1606250A	更新图面	06/29/2016	SHEET: 1/1	MATERIAL:		 昆山捷皇电子精密科技有限公司 HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.	
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE	