



- NOTES:
- MATERIAL:  
 BODY: HI-TEMP. PLASTIC, BLACK, UL 94V-0  
 TERMINAL: COPPER ALLOY, T=0.10mm  
 SHELL: STAINLESS STEEL T=0.15mm
  - FINISH:  
 TERMINA: 50u" MIN Ni UNDERPLATING OVERALL  
 GOLD FLASH ON CONTACT AREA  
 GOLD FLASH ON SOLDER TAIL AREA  
 SHELL: 50u" MIN Ni UNDERPLATING OVERALL  
 GOLD FLASH ON SOLDER TAIL AREA
  - ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
  - RESISTANCE TO CURRENT: 3A MAX
  - ALL DIMENSIONS MARKED (XX) MUST BE MEASURED BY FAI.

P/N	DIM A (mm)
B36-AB03F231	1.00
B36-AB03F235	1.50

REV.	ECN NO.	DESCRIPTION	DATE	UNITS: mm	GENERAL TOLERANCE	DRAW:	PART NO:
				DATE: 03/11/2013	X. ±0.25 X' ±0.20 .XX ±0.10 .XXX ±0.05	CHECKED:	B36-AB03F23X
				SCALE: 8:1	X" ±2.00' X' ±1.00' .XX' ±0.50' .XXX' ±0.10'	APPROVE:	NAME: 总高度2.30H 测压式 板上1.00H/1.50H 电池座
				SHEET: 1/1	TITLE:		DRAWING NO: C-B36-0000_E
				REV. A	FINISH: SEE NOTE	<b>昆山捷皇电子精密科技有限公司</b> HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.	