


- NOTES:
- MATERIAL:
HOUSING: NYLON-9T (全新材料), BLACK, UL 94V-0
TERMINAL: COPPER ALLOY OR STAINLESS STEEL
 - FINISH:
CONTACT: 15u" Min Au PLATED ON CONTACT
1u" Min Au PLATED ON SOLDER TAILS AREA
50u" Min Ni UNDER PLATED OVER ALL
 - ALL DIMENSIONS MARKED ∇ MUST BE CONTROLLED EVERYDAY BY QC.
MARKED ∇ PER WORK WEEK AND MARKED ∇ PER MONTH MUST BE CONTROLLED.
 - ALL DIMENSIONS MARKED (XX) MUST BE MEASURED BY FAI
 - PRODUCT SPECIFICATIONS:
5-1 WITHSTANDING: 500VAC/MINUTE
5-2 CONTACT RESISTANCE: 50 MILLIOHM (initial) Max.
5-3 INSULATION RESISTANCE: 100 MEGOHM Min.
5-4 MATING FORCE: 5-20 N (BTFORE DURABILITY)
3-20 N (AFTER DURABILITY)
5-5 UNMATING FORCE: 7-20 N (BTFORE DURABILITY)
5-20 N (AFTER DURABILITY)
 - 5-6 OPERATION TEMPERATURE: -25° TO +85°
 - 5-7 STORAGE TEMPERATURE: -25° TO +85°
 - 5-8 DURABILITY: 5000 CYCLES



D/C PART NO.:

H=HRD
A=Au 5U"
B=Au 15U"
年: 7=2017年
8=2018年
9=2019年

线别: A=A线、B=B线.....
班别: 1=白班
2=夜班
日: 1=1日, 2=2日.....
A=10日, B=11日.....
(WITH OUT 1、O、Z)
月: 1=1月, 2=2月.....
A=10月, B=11月.....

NAME	MATERIAL	FINISH	Q'TY
HOUSING	NYLON-9T(全新材料),BLACK,UL 94V-0		1
Mylar	KAPTON T=0.06mm	/	1
PEG	SUS304-H T=0.15mm	/	1
DETECT	SUS304-3/4H T=0.20mm	50U" MIN Ni UNDER PLATED OVER ALL 15U" MIN AU ON CONTACT AREA 1U" MIN AU ON SOLDER AREA	1
L AUDIO			1
R AUDIO			1
GND	C5210-H T=0.20mm		1
MIC			1

REV.	ECN NO.	DESCRIPTION	DATE	UNITS: mm	GENERAL TOLERANCE	DRAW:	PART NO:
A		NEW	09/02/2017	DATE: 09/02/2017	X. ±0.20 .X ±0.15 .XX ±0.10 .XXX ±0.05	CHECKED:	PH83-0A22C38M
				SCALE: 5/1	X' ±2.00' .X' ±1.00' .XX' ±0.50'	APPROVE:	TITLE: Ø3.50MM PHONE JACK CONN. 板上2.20mm·H=3.80mm
				SHEET: 1/1	MATERIAL:		DRAWING NO:
				REV. A	FINISH: SEE NOTE		



昆山捷皇电子精密科技有限公司
HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.